

Stoner**Stoner® S261
SPINNERET LUBRICANT**

Product Description

Stoner® S261 SPINNERET LUBRICANT is specially formulated to lubricate spinneret dies when extruding synthetic fibers. Permits smooth spinneret operation and improves spinneret performance by providing long lasting lubrication, even when die temperatures exceed 600°F. Contains a high-quality, heat stable lubricant that will not vaporize, oxidize, or burn-off during spinneret operation. Use before start-up of die to prevent hang-ups and residue build-up.

This product uses advanced aerosol propellant technology to provide optimum performance without using ozone depleting chemicals. Contains no chlorinated solvents or environmentally harmful chlorofluorocarbon (CFC) solvents or propellants. efficiency in many processes including injection, compression, transfer, vacuum form, pour cast, die cast, and extrusion molding.

S261 SPINNERET LUBRICANT ADVANTAGES:

- Lets you make more high quality fiber and less scrap.
- Extends time between die scraping and cleaning.
- Contains no CFC or HCFC solvents or propellants.
- Contains no Class I or Class II ozone depleting substances or chlorinated solvents such as methylene chloride or 1,1,1 trichloroethane.
- Colorless, non-staining.

Uses

S261 SPINNERET LUBRICANT used to lubricate spinneret dies when extruding synthetic fibers.

Direction for Use

Recommended Procedure

ALWAYS HOLD CAN UPRIGHT WHEN SPRAYING. Do not turn can upside down or sideways when spraying or propellant alone will vent and may result in unsafe conditions. Shake can well. 1) For trigger spray actuator, remove safety tab on top and squeeze trigger to spray. 2) For vertical spray actuator, push spray head toward black dot on top of rim. Hold can 10 to 12 inches from surface to be sprayed. Apply a thin coating on surface for best results.

Storage and Handling

Do not puncture or incinerate container. Do not expose container to heat or store at temperatures above 120 °F. This product is classified as nonflammable by ASTM testing method D3065-01. However, contents of this container can ignite under certain circumstances. Keep container away from and do not use near sparks, open flame, heated surfaces, or other ignition sources.

Packaging

S261 SPINNERET LUBRICANT is available in:

- 12 can case of 12 oz cans Part # S261

Technical Assistance

Call: 800-227-5538 or 1 (717) 786-7355
Email: TimeSaver@StonerSolutions.com
Visit: StonerSolutions.com

The information contained in this TDS is believed to be accurate and reliable. It is recommended that each user test the material and procedures prior to initial use. Nothing stated in this TDS is to be construed as a warranty either expressed or implied.