## **Safety Data Sheet**

# E202 Dry Mist Silicone Mold Release<sup>TM</sup>



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

## 1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538 Product Name: Dry Mist Silicone Mold Release<sup>TM</sup>

Product Code: E202

Product Use: Mold Release

24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

### 2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification Gases under pressure - Liquified Gas

Flammable Aerosol Category 2

Signal Word Warning

Hazard Statements Flammable aerosol.

Contains gas under pressure; may explode if heated.

**Precautionary Statements** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

**Storage** Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do no expose to temperatures exceeding  $50^{\circ}\text{C}/\ 122^{\circ}\text{F}.$ 

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTCAS #PercentHalogenated hydrocarbon/ether blendMixture80-100

HMIS® III\* HAZARDOUS WARNINGS:

Health: 1 Flammability: 2 Physical: 1 Personal See Section 8

Protective Equipment:

## 4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there

is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if

symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.

Ingestion: Ingestion is an unlikely route of exposure. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical

attention.
NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life

Stoner Incorporated E202 PAGE 1

<sup>\*</sup> See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

#### 5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that

are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or

explode under fire conditions.

Fire Fighting Instructions: Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may

be used from a safe distance to cool closed containers and protect surrounding area.

#### 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

## 7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or

repeated breathing of vapor. May cause frostbite.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Empty

container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and

possible ignition sources.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the MSDS (from

known, suspected or apparent adverse effects).

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as

chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or

airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with

skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved

respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

COMPONENT CAS# ACGIH TLV OSHA PEL OTHER

Halogenated hydrocarbon/ether blend Mixture Not established Not established 1000ppm TWA (Mfr.)

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Aerosol can Lower Flammability Limit (%): Not applicable Appearance: Clear Colorless Upper Flammability Limit (%): Not applicable Odor: Slight ethereal. 76.00 Vapor Pressure (PSIG @ 70°F): Odor Threshold: Mild Vapor Density [air = 1]: 2.02 Relative Density (H2O=1): 0.8 pH: Not applicable

Melting/Freezing Point (°F): No data available Solubility in Water: Negligible; 0-1% Boiling Point (°F): No data available Partial Coefficient: n- No data available

octanol/water:

Flash Point (°F PMCC): Not applicable Autoignition Temperature (°F): 622

Evaporation Rate: 0.1-0.5 (n-Butyl acetate = 1) Decomposition Temperature (°F): No data available Flammability (solid, gas): No data available Viscosity, dynamic (cSt): No data available

Percent VOCs (%): 40 - 60

#### 10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Alkali. Alkaline earth metals. Powdered metals. Ignition sources such as open flames, sparks, static

discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides.

Decomposition Products: This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming

hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute

toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm.

#### 11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental No data available.

Toxicity:

Ether propellant

Ingredient CAS # Toxicological Data

Halogenated hydrocarbon Mixture ORAL ALD Rat > 1500 mg/kg

115-10-6

4HR ALC Rat 383000 ppm Inhalation LC50 Rat = 164000 ppm

Stoner Incorporated E202 PAGE 2

## 12. ECOLOGICAL INFORMATION

**Ecological Toxicity:** No data available Mobility: No data available

CAS# **Toxicological Data** Ingredient

Ether propellant 115-10-6 48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L

#### 13. DISPOSAL CONSIDERATIONS

Disposal: Dispose according to Federal, State and local regulations.

## 14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

<sup>† &</sup>quot;Limited Quantities" may be applicable for this transportation mode.

#### 15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT CAS# % BY WEIGHT **Regulatory Body** SARA Section 313

No components listed in this section.

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below. Prop65 Cancer No components listed in this section.

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below. No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

#### 16. OTHER INFORMATION

Other Information: MSDS Prepared by L. Dean Swartz, MSDS Coordinator

06/03/15 Version Date:

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

E202 PAGE 3 Stoner Incorporated