Safety Data Sheet E313 Release & PaintTM



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION Stoner Incorporated Product Name: Release & Paint[™] E313 1070 Robert Fulton Hwy. Product Code: Quarryville, PA 17566 Product Use: Mold Release 1-800-227-5538 1-800-424-9300 [CHEMTREC] 24-hour emergency phone: 2. HAZARD IDENTIFICATION POTENTIAL HEALTH EFFECTS Classification of the chemical in accordance with paragraph (d) of §1910.1200; GHS Hazard Symbols **GHS** Classification Gases under pressure - Liquified Gas Flammable Aerosol Category 2 Signal Word Warning **Hazard Statements** Flammable aerosol. Contains gas under pressure; may explode if heated. **Precautionary Statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Prevention Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Storage Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

3. COMPOS	ITION/INFORM	ATION ON ING	REDIENTS				
COMPONENT Halogenated hydr	rocarbon/ether blend	<u>CAS</u> Mixtu			Percent 80-100		
HMIS® III* HAZ Health: 1	ZARDOUS WARNING	S: Flammability: 2		Physical:	1	Personal Protective Equipment:	See Section 8
-	org/hmis or call the NPC D MEASURES	CA at 1 (202) 462-6272	2 for more informat	ion on this current rating s	ystem.		
Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.						
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.						
Ingestion:	Ingestion is an unlikely route of exposure. Do not induce vomiting unless instructed by a physician. Rinse mouth thoroughly with water.						
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.						
NOTES TO DUNG	ICIAN						

NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life *Stoner Incorporated PAGE 1*

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.Containers may rupture or explode under fire conditions.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. May cause frostbite. Combustible. Keep away from heat and flame. Normal precautions common to safe manufacturing practice should be followed in handling and storage.
 Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion

container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use. Keep from extreme temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the MSDS (from					
Eye Protection:	known, suspected or apparent adve Wear chemically resistant safety gl	asses with side shields when h	0 1	3 1		
	chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.					
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.					
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. If respiratory irritation develops below the recommended exposure limits, use an NIOSH approved nuisance dust/mist/organic vapor respirator.					
COMPONENT	CAS #	ACGIH TLV	OSHA PEL	OTHER		
Halogenated hydrocarbon/ether		Not established	Not established	1000ppm TWA (Mfr.)		

9. PHYSICAL AND CHEMICAL PROPERTIES

Aerosol can	Lower Flammability Limit (%):	Not applicable
Clear Colorless	Upper Flammability Limit (%):	Not applicable
Slight ethereal.	Vapor Pressure (PSIG @ 70°F):	79.00
Mild	Vapor Density $[air = 1]$:	2.01
Not applicable	Relative Density (H2O=1):	0.8
No data available	Solubility in Water:	Negligible; 0-1%
No data available	Partial Coefficient: n- octanol/water:	No data available
Not applicable	Autoignition Temperature (°F):	622
0.1-0.5 (n-Butyl acetate = 1)	Decomposition Temperature (°F):	No data available
No data available 40 - 60	Viscosity, dynamic (cSt):	No data available
	Clear Colorless Slight ethereal. Mild Not applicable No data available No data available Not applicable 0.1-0.5 (n-Butyl acetate = 1) No data available	Clear ColorlessUpper Flammability Limit (%):Slight ethereal.Vapor Pressure (PSIG @ 70°F):MildVapor Density [air = 1]:Not applicableRelative Density (H2O=1):No data availableSolubility in Water:No data availablePartial Coefficient: n- octanol/water:Not applicableAutoignition Temperature (°F):0.1-0.5 (n-Butyl acetate = 1)Decomposition Temperature (°F):No data availableViscosity, dynamic (cSt):

10. STABILITY AND REACTION

Chemical Stability: Conditions to Avoid:	Stable. Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Formaldehyde. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Reproduction (2-gen rat) Reduced Fertility: 20,000 ppm - Reduced body wt: 20,000 ppm. Toxicity:

Ingredient Halogenated hydrocarbon	CAS # Mixture	Toxicological Data ORAL ALD Rat > 1500 mg/kg AUD AL C Part 282000 ppm			
Ether propellant	115-10-6	4HR ALC Rat 383000 ppm Inhalation LC50 Rat = 164000 ppm			
12. ECOLOGICAL INFOR	RMATION				
	o data available o data available				
Ingredient Ether propellant	CAS # 115-10-6	Toxicological Data 48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L			
13. DISPOSAL CONSIDE	RATIONS				
Disposal : Dispose according to Federal, State and local regulations.					
14. TRANSPORTATION I	NFORMATION				
AgencyUN NumberDOTUN1950IATAID8000IMDGUN1950† "Limited Quantities" may be applied	Proper Shipping name Aerosols, Flammable† Consumer Commodity† Aerosols, Flammable† eable for this transportation mode.	Hazard Class 2.1 9 2.1	Packing Group Not applicable Not applicable Not applicable		
15. REGULATORY INFO	RMATION				
Warning: This product contains the COMPONENT No components listed in this section	CAS #	brting requirements for the following regulator % BY WEIGHT Regulatory Boo SARA Section 3	ły		
Warning: This product may contain chemicals known to the State of California to cause cancer. See list below. No components listed in this section. Prop65 Cancer					
Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below. No components listed in this section. Prop65 Birth Defects					
All components of this product are listed on the TSCA inventory.					
16. OTHER INFORMATION					
Other Information : MSDS Prepared by L. Dean Swartz, MSDS Coordinator					

Version Date: 06/03/15

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.