Safety Data Sheet

E455 Thermoset Mold Release



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538 Product Name: Thermoset Mold Release

Product Code: E455

Product Use: Mold Release

24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols





GHS Classification Gases under pressure - Liquified Gas

Aspiration Hazard Category 1 Flammable Aerosol Category 2

Signal Word Danger

Hazard Statements Flammable aerosol.

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

Precautionary Statements

Prevention Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor/....

Do NOT induce vomiting.

Storage Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do no expose to temperatures exceeding $50^{\circ}\text{C}/\ 122^{\circ}\text{F}.$

Disposal Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

 COMPONENT
 CAS #
 Percent

 Petroleum distillates
 64742-89-8
 40 - 60

 Halogenated hydrocarbon
 75-37-6
 20 - 40

HMIS® III* HAZARDOUS WARNINGS:

Health: 2* Flammability: 3 Physical: 1 Personal See Section 8

Protective Equipment:

^{*} See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there

is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if

symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse.

Ingestion: Do not induce vomiting unless instructed by a physician. If vomiting occurs spontaneously, keep head below hips to prevent

aspiration of liquid into lungs. Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. Ingestion is

an unlikely route of exposure.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and

quiet. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier

than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under

fire conditions.

Fire Fighting Instructions: Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may

be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Place waste material into container and close it tightly. Dispose of container properly. Wear appropriate clothing.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid prolonged or

repeated breathing of vapor. May cause frostbite.

Storage: Keep away from heat, sparks and flame. Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at

temperatures above 120 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials

such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the MSDS (from

known, suspected or apparent adverse effects).

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as

chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or

airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with

skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved

respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

COMPONENTCAS #ACGIH TLVOSHA PELOTHERPetroleum distillates64742-89-8300 ppm300 ppmNot established

Halogenated hydrocarbon 75-37-6 Not established Not established 1000ppm TWA (Mfr.)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Aerosol can Lower Flammability Limit (%): Not applicable Appearance: White to off-white Upper Flammability Limit (%): Not applicable 63.0 70.00 Odor: Petroleum solvent Vapor Pressure (PSIG @ 70°F): Odor Threshold: Moderate Vapor Density [air = 1]: 3.06 Relative Density (H2O=1): Not applicable 0.8 pH:

Melting/Freezing Point (°F): No data available Solubility in Water: Not determined Boiling Point (°F): No data available Partial Coefficient: n- 2.13-4.85

octanol/water:

Flash Point (°F PMCC): Not applicable Autoignition Temperature (°F): 246

Evaporation Rate: 0.5-2 (n-Butyl acetate = 1) Decomposition Temperature (°F): No data available

Flammability (solid, gas): No data available Viscosity, dynamic (cSt): 0.7

Percent VOCs (%): 60 - 80

Stoner Incorporated E455 PAGE 2

10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.

Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming

hydrofluoric acid and carbonyl fluoride.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental No data available.

Toxicity:

Ingredient CAS # Toxicological Data

Halogenated hydrocarbon 75-37-6 ORAL ALD Rat > 1500 mg/kg 4HR ALC Rat 383000 ppm

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available Mobility: No data available Degradability: Biodegradable.

Ingredient CAS # Toxicological Data

No data available

13. DISPOSAL CONSIDERATIONS

Disposal: Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

^{† &}quot;Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT CAS # % BY WEIGHT Regulatory Body
No components listed in this section. SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

16. OTHER INFORMATION

Other Information: MSDS Prepared by L. Dean Swartz, MSDS Coordinator

Version Date: 06/15/15

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

Stoner Incorporated E455 PAGE 3