Safety Data Sheet X-9032/G401 Nix Stix® Mold Release



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy		Product Name: Product Code:	Nix Stix® Mold Release X-9032/G401			
Quarryville, PA 17566 1-800-227-5538		Product Use: 24-hour emergency phone:	Mold Release 1-800-424-9300 [CHEMTREC]			
2. HAZARD IDENTIFIC	ATION					
POTENTIAL HEALTH EFFECT						
Classification of the chemical in a GHS Hazard Symbols						
GHS Classification	Flammable	Gases under pressure - Liquified Gas Flammable Aerosol Category 2 Serious Eye Damage/Eye Irritation Category 2A				
Signal Word	Warning					
Hazard Statements		aerosol. s under pressure; may explode if heated. pus eye irritation.				
Precautionary Statements						
Prevention	Do not spray Pressurized P264 - Wasl	from heat/sparks/open flames/hot surfaces / on an open flame or other ignition sourc container: Do not pierce or burn, even aft n thoroughly after handling. tive gloves/protective clothing/eye protec	er use.			
Response	Continue rir	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.				
Storage		Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.				

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT Halogenated hydrocarbon/ether blend Solvent propellant	<u>CAS #</u> Mixture 102687-65-0		<u>Percent</u> 60 - 80 1-20		
HMIS® III* HAZARDOUS WARNINGS: Health: 2 Fl	lammability: 2	Physical:	2	Personal Protective Equipment:	See Section 8

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

X-9032/G401

4. FIRST AI	D MEASURES
Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there
	is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. For liquid contact, treat for
Skill Colliact.	In case of contact, inimited atter wash containinated area with prenty of water for at least 15 initiates. For inquite contact, theat for

PAGE 1

Stoner Incorporated

frostbite if necessary. Seek medical attention if symptoms persist. Wash clothing before reuse.Ingestion:Ingestion is an unlikely route of exposure. Contact a physician, medical facility, or poison control center for advice on whether to
induce vomiting.Inhalation:Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical
attention.

NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. Treatment is symptomatic and supportive.

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.Containers may rupture or explode under fire conditions. Hazardous decomposition products may be formed (see Sec.10). This material burns with difficulty, but will
Fire Fighting Instructions:	support combustion. "Empty" containers retain product residue and can be dangerous. Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus. Avoid breathing the products and substances that may result from the thermal decomposition of the product or other substances in the fire zone.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required.

7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. May cause frostbite. Usual precaution for combustible liquids. Wash hands thoroughly after handling. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 122 degrees F. Empty

container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use. Store away from heat and direct sunlight. This material (or a component) evolves flammable methyl alcohol when exposed to water or humid air. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).						
Eye Protection:	Wear chemica chemical spla airborne mate	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available. The use of safety glasses with side shields is recommended if there is any probability of liquid contact with the eyes.					
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact v skin.						
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. The use of an approved dust, fume a mist respirator designed for exposure limits greater than 0.05 mg/m3 is recommended.						
COMPONENT		<u>CAS #</u>	ACGIH TLV	OSHA PEL	OTHER		
Halogenated hydrocarbon/ether	r blend	Mixture	Not established	Not established	1000ppm TWA (Mfr.)		
Solvent propellant		102687-65-0	Not established	Not established	800 ppm (mfr. recommend)		

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Appearance:	Aerosol can Clear Colorless	Lower Flammability Limit (%): Upper Flammability Limit (%):	Not applicable Not applicable
Odor: Odor Threshold:	Slight ethereal. Mild	Vapor Pressure (PSIG @ 70°F): Vapor Density [air = 1]:	Not determined
pH:	Not applicable	Relative Density $(H2O=1)$:	>1 0.88
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n- octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	Not applicable
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas): Percent VOCs (%):	No data available 1-20	Viscosity, dynamic (cSt):	No data available

10. STABILITY AND REACTION

Chemical Stability: Conditions to Avoid:	Stable. Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides. Sparks, open flame, other ignition sources, and elevated temperatures. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure. Strong oxidizing agents.
Decomposition Products:	This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Hydrogen chloride. Hydrogen Chloride. Various hydrocarbons. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.		
Ingredient	CAS #	Toxicological Data	
Halogenated hydrocarbon	Mixture	ORAL ALD Rat > 1500 mg/kg	
		4HR ALC Rat 383000 ppm	
Ether propellant	115-10-6	Inhalation LC50 Rat = 164000 ppm	
Solvent propellant	102687-65-0	No data available	
		Inhalation LC50 (4h) Rat 120000 ppm	

12. ECOLOGICAL INFORMATION

Ecological Toxicity: Mobility:	No data available No data available		
Ingredient Ether propellant		CAS # 115-10-6	Toxicological Data 48HR NOEC GUPPIES > 4000 mg/L
Solvent propellant		102687-65-0	48HR NOEC Daphnia > 4000 mg/L Aquatic LC50 (96h) Rainbow Trout 38 mg/L 48HR EC50 Daphnia 82 mg/L 72HR EC50 Algae 106.7 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION Agency **UN Number Proper Shipping name** Hazard Class **Packing Group** DOT UN1950 Not applicable Aerosols, Flammable† 2.1 IATA ID8000 Consumer Commodity* 9 Not applicable UN1950 2.1 IMDG Aerosols, Flammable[†] Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below: COMPONENT % BY WEIGHT CAS # **Regulatory Body** No components listed in this section.

	· · · · · · · · · · · · · · · · · · ·										
							1			G 116	
w	arning.	This n	roduct	mav	contain	chemicals	known	to the S	state of	('aliforn	12

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below. No components listed in this section.

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below. No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

X-9032/G401

PAGE 3

SARA Section 313

Prop65 Cancer

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 07/12/16

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.