Stoner[®] G480 RR 1381

Water-Based Release System

Product Description

Stoner[®] **G480 RR 1381** is a silicone polymer release emulsion that gives outstanding results for tire release applications. RR 1381 WBA helps reduce rust and corrosion in steel molds.

G480 RR 1381 ADVANTAGES:

- No transfer -- post-finishing problems virtually eliminated.
- No knit lines, cracks, or splits -- low scrap rate.
- Very low build-up -- more production time between mold cleanings.

Uses

Stoner[®] G480 RR 1381 is for application to mold surfaces above 212°F at the time of application:

- PlasticsMetal
- Rubber

Direction for Use

Recommended Procedure

RR 1381 WBA can best be applied by using a fine mist spray. Clean, rinse, and dry mold thoroughly. Apply three light coats of RR 1381 WBA at molding temperature. Allow 5 minutes between coats. Repeat as needed, using one1 light coat, normally at break time.

Storage and Handling

Store below 90°F and KEEP FROM FREEZING.

Packaging

Stoner® G480 RR 1381 is available in:

- 1-gallon Part # G480GL
 5-gallon pails Part # G480PL
- 55-gallon pails Part # G480DR

Technical Assistance

Call: 800-227-5538 or 1 (717) 786-7355 Email: CustomerService@StonerSolutions.com Visit: StonerMolding.com

NO RISK GUARANTEE. Stoner Molding guarantees 100% satisfaction or your money back. If you're ever dissatisfied with any Stoner Molding product, simply return the unused portion for a full refund.



