

Stoner**Stoner® S284**
SPINMAX™ SPINNERET LUBRICANT

Product Description

Stoner® S284 SPINMAX™ SPINNERET LUBRICANT is specifically formulated to lubricate spinneret dies when extruding synthetic fibers. Permits smooth spinneret operation, makes scrapes faster and easier, and improves spinneret performance by providing long lasting lubrication, even when die temperatures exceed 600°F. Contains a high-quality, heat stable lubricant that will not vaporize, oxidize, or burn-off during spinneret operation. Use before start-up of die to prevent hang-ups and residue build-up. This spinneret lubricant uses advanced aerosol propellant technology to provide optimum performance without using flammable solvents or propellants. Contains no chlorinated solvents or environmentally harmful chlorofluorocarbon (CFC or HCFC) solvents or propellants. No reporting is required under Section 313 of US EPA SARA Title III. Non-flammable aerosol.

S284 SPINMAX™ SPINNERET LUBRICANT ADVANTAGES:

- Lets you make more high quality fiber and less scrap.
- Extends time between die scraping and cleaning.
- Safer, non-flammable and non-staining.
- Low mist spray.

Uses

S284 SPINMAX™ SPINNERET LUBRICANT used to lubricate spinneret dies when extruding synthetic fibers.

Direction for Use

Recommended Procedure

ALWAYS HOLD CAN UPRIGHT WHEN SPRAYING. Do not turn can upside down or sideways when spraying or propellant alone will vent and may result in unsafe conditions. Shake can well. 1) For trigger spray actuator, remove safety tab on top and squeeze trigger to spray. 2) For vertical spray actuator, push spray head toward black dot on top of rim. Hold can 10 to 12 inches from surface to be sprayed. Apply a thin coating on surface for best results.

Storage and Handling

Do not puncture or incinerate container. Do not expose container to heat or store at temperatures above 120 °F. This product is classified as nonflammable by ASTM testing method D3065-01. However, contents of this container can ignite under certain circumstances. Keep container away from and do not use near sparks, open flame, heated surfaces, or other ignition sources.

Packaging

S284 SPINMAX™ SPINNERET LUBRICANT is available in:

- 12-can case of 12 oz cans Part # S284

Technical Assistance

Call: 800-227-5538 or 1 (717) 786-7355

Email: TimeSaver@StonerSolutions.com

Visit: StonerMolding.com

NO RISK GUARANTEE. Stoner Molding guarantees 100% satisfaction or your money back. If you're ever dissatisfied with any Stoner Molding product, simply return the unused portion for a full refund.



Stoner Molding Solutions
You Mold It. We Release It.