Material Safety Data Sheet E204 Light Duty Silicone Mold ReleaseTM



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION							
Stoner Incorporated		I	Product Name:	Light Duty Silicone Mo	ld Release™		
1070 Robert Fulton Hwy.		1	Product Code:	E204			
Quarryville	e, PA 17566		Version Date:	10/10/13			
1-800-227-		2	24-hour emergency phone:	1-800-424-9300 [CHEMTREC]			
2. COMPOSITION / INFORMATION ON INGREDIENTS							
				Exposure Limits			
COMPONENT	1 / 1 11 1	<u>CAS #</u> Mixture	ACGIH TLV Not established	OSHA PEL Not established	OTHER		
	rocarbon/ether blend		Not established	Not established	1000ppm TWA (Mfr.)		
	DS IDENTIFICATI						
			ECTS OF OVEREXPOSURE				
Eye : Skin :	May cause eye irritation. Liquid may cause frostbit		clude stinging, tearing, and redness.				
Ingestion :	1 5		of exposure. No evidence of harmfu	il effects from available informati	ion		
Ingestion : Ingestion is not considered a potential route of exposure. No evidence of harmful effects from available information. Inhalation : Breathing small amounts during handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Inhalation of							
			its may cause temporary central nerv				
	dizziness, headache, inco	ordination, and los	s of consciousness. Exposure to high	h concentrations can cause irregul	lar heartbeat, cardiac arrest		
	and death.						
	HRONIC [long term] HEA		F OVEREXPOSURE:				
General Effects: Cancer Informati	No chronic healt		COMPONENTS LISTED AS CAR	CINCENIC BY LARC NTR C	DP OSHA 1010(7)		
Mutagenicity:			ct or any components present at grea				
	DITIONS AGGRAVATE			ator than 0.170 is indugenie of ger	liotonie.		
			cardiovascular system may have ine	creased susceptibility to the toxic	ity of excessive exposures.		
HMIS® III* HAZ	ZARDOUS WARNINGS:						
Health: 1	Flammability:		5	nal Protective Equipment: See S	ection 8		
* See www.paint.c	org/hmis or call the NPCA	at 1 (202) 462-627	72 for more information on this curr	ent rating system.			
4. FIRST A	ID MEASURES						
Eyes:			of water for at least 15 minutes wh	ile holding eyelids apart. If symp	otoms persist or there is		
Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if					· 1		
Skin Contact:			if symptoms persist. Wash clothing				
	necessary.	. medicai atteitti0ii	ii symptoms persist. wasn clouning	before reuse. For inquite contact,			
Ingestion:		route of exposure	. Contact a physician, medical facili	ty, or poison control center for ad	vice on whether to		
6			mouth if victim is rapidly losing con				
Inhalation:			e artificial respiration. If breathing is				
attention.							
NOTES TO PHY	YSICIAN:						

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other			
	, , , , , , , , , , , , , , , , , , , ,	rom the material's handling point.Containers may rupture or explode		
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.			
Flash Point:	Not applicable°F PMCC	°C PMCC		
Lower Flammability Limit:	Not applicable			
Upper Flammability Limit:	Not applicable			
Autoignition Temperature:	Not applicable			
Aerosol Flame Projection Test:	Non-flammable aerosol, as determined by ASTM D3065-94. However, this product contains components which may be jonited under certain circumstances. Do not use near ignition sources such as sparks or open flames.			

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION				
Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated in "Section 8" of this MSDS (from known, suspected or apparent adverse effects).			
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.			
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.			
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.			

Vapor Density:

Boiling Point:

pH:

Evaporation Rate: Solubility in Water: [air = 1] 2.00

Negligible; 0-1%

Not applicable

No data available°F

0.1-0.5 (n-Butyl acetate = 1)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:Aerosol canAppearance:Clear ColorlessOdor:Slight ethereal.Specific Gravity:0.80 (H2O=1)Vapor Pressure:76.0 PSIG @ 70°F

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals. Ignition
	sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides.
Decomposition Products:	This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur.

11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION					
Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group	
DOT	Aerosols, non-flammable *	UN1950	2.2	Not applicable	
IATA	Aerosols, non-flammable *	UN1950	2.2	Not applicable	
IMDG	Aerosols, non-flammable *	UN1950	2.2	Not applicable	

* "Limited Quantities" may be applicable for this transportation mode.

13. REGULATORY INFORMATION

 Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:
 COMPONENT
 CAS #
 % BY WEIGHT
 Regulatory Body

 No components listed in this section.
 SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below. No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below. No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.