

Material Safety Data Sheet

P448 Heavy Duty Mold Release

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538	Product Name:	Heavy Duty Mold Release
	Product Code:	P448
	Version Date:	06/02/11
	24-hour emergency phone:	1-800-424-9300 [CHEMTREC]

2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	Exposure Limits	
			OSHA PEL	OTHER
Water	7732-18-5	Not established	Not established	Not established
NJ Trade Secret Registry	#80100382-5048P	Not established	Not established	Not established
Polydimethylsiloxane emulsion	MIXTURE	Not established	Not established	Not established
NJ Trade Secret Registry	#80100382-5145P	Not established	1000ppm	Not established
NJ Trade Secret Registry	#80100382-5144P	Not established	Not established	Not established

3. HAZARDS IDENTIFICATION

POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

- Eye : May cause eye irritation. Symptoms may include stinging, tearing, and redness.
Skin : Skin contact may cause irritation.
Ingestion : May be harmful if swallowed. If swallowed symptoms may include: Gastrointestinal irritation (such as nausea, vomiting, and diarrhea). Discomfort due to volatility would be expected.
Inhalation : When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm. Inhalation can cause nose, throat, and respiratory tract irritation, coughing and headache.

POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

- General Effects: Adverse liver and reproductive effects reported in animals.
Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)
Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

May aggravate liver and kidney.

HMSI® III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 1 Physical: 0 Personal Protective Equipment: See Section 8

* See www.paint.org/hmsi or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

- Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion: Contact a physician, medical facility, or poison control center immediately. Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

NOTES TO PHYSICIAN:

Treatment is symptomatic and supportive.

5. FIRE FIGHTING MEASURES

- Fire and/or Explosion Hazards: Product is predominately water, and is not flammable. The solid ingredients are difficult to ignite. Hazardous decomposition products may be formed (see Sec.10). Product is water based material, containing minor amounts of flammable ingredients.
Fire Fighting Instructions: Use water spray, foam, dry chemical, or CO2. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.
Flash Point: None°F PMCC None°C PMCC
Lower Flammability Limit: No data available
Upper Flammability Limit: No data available
Autoignition Temperature: No data available

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

- Handling: Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid contact with eyes. Spilled material is quite slippery. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin.

Storage: Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Keep from extreme temperatures. Keep from freezing. Do not store at temperatures above 80 degrees F.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects).

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: No respiratory protection required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk liquid	Vapor Density:	[air = 1] 0.97
Appearance:	White Slightly opaque	Evaporation Rate:	0.02-0.1 (n-Butyl acetate = 1)
Odor:	None to very faint	Solubility in Water:	Complete; 100%
Specific Gravity:	1.00 (H2O=1)	Boiling Point:	212°F
Vapor Pressure:	Not Applicable PSIG @ 70°F	pH:	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Conditions to Avoid: None known.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Oxides of siloxanes. Formaldehyde.

11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Not regulated by agency			
IATA	Not regulated by agency			

13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.
No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.
No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.