
# Safety Data Sheet A324 Rapid Release<sup>TM</sup>



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.



A324

3. COMPOSITION/INFORMA	TION ON INGREDIENTS			
<u>COMPONENT</u>	CAS#	Perc		
Hydrocarbon propellant	68476-86-8	80 -	100	
Silicone polyether copolymer	#80100382-5096P	1-20	)	
Aliphatic hydrocarbon	64741-66-8	1-20	)	
Petroleum distillates	8052-41-3	1-20	)	
HMIS® III* HAZARDOUS WARNINGS	3:			
Health: 1	Flammability: 4	Physical: 0	Personal Protective Equipment:	See Section

\* See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES			
Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.		
Skin Contact:	For liquid contact, treat for frostbite if necessary. In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse.		
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.		
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.		

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions);

5. FIRE FIGHTING MEASURES			
Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.		
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self- contained breathing apparatus.		

#### 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

### 7. HANDLING AND STORAGE

Handling: This material can be harmful or irritating. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not use near ignition sources.
Storage: Do not store at temperatures above 120 degrees F. Store away from incompatible materials such as materials that support combustion

Storage: Do not store at temperatures above 120 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation is required to maintain operator exposure below published exposure limits. Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the MSDS (from known, suspected or apparent adverse			
	effects).			
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such			5 1
	chemical splash goggles and/or face sh	1 2	, I	shing or spraying liquid or
	airborne material. Do not wear contact lenses. Have an eye wash station available. The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with			
Skin Protection:	, e	is recommended if there is	any possibility of prolonged	or repeated liquid contact with
Decrinatory Ductastion	skin. A supplied air respirator should be use	d if wantilation is not suffici	iont to maintain avecause lim	ta Usa NIOSU approved
Respiratory Protection:	respirator where there is likelihood of i		1	its. Use MOSH approved
	respirator where there is fixelihood of i	initiation of the product in	ist, spray of acrosof.	
<u>COMPONENT</u>	<u>CAS #</u>	ACGIH TLV	OSHA PEL	<u>OTHER</u>
Hydrocarbon propellant	68476-86-8	1000ppm	Not established	Not established
Silicone polyether copolymer	#80100382-5096P	Not established	Not established	Not established
Aliphatic hydrocarbon	64741-66-8	Not established	500ppm TWA	300ppm TWA-Mfr.
				Recommended
Petroleum distillates	8052-41-3	100 ppm TWA	500 ppm	Not established

Lower Flammability Limit (%):

Upper Flammability Limit (%):

Vapor Pressure (PSIG @ 70°F):

Autoignition Temperature (°F):

Decomposition Temperature (°F):

Vapor Density [air = 1]:

Solubility in Water:

octanol/water:

Partial Coefficient: n-

Viscosity, dynamic (cSt):

Relative Density (H2O=1):

Not applicable

Not applicable

Negligible; 0-1%

No data available

No data available

No data available

Not applicable

56.00

2.01

0.76

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Aerosol can

Cloudy white

Not applicable

Not applicable

80 - 100

Not determined

No data available

No data available

No data available

Mild

Petroleum solvent

Physical State:
Appearance:
Odor:
Odor Threshold:
pH:
Melting/Freezing Point (°F):
Boiling Point (°F):
Flash Point (°F PMCC):
Evaporation Rate:
$\mathbf{F}^{1}$

Evaporation Rate: Flammability (solid, gas): Percent VOCs (%):

# **10. STABILITY AND REACTION**

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing
	metal surfaces.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Oxides of siloxanes.
	Formaldehyde. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product
	can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the
	respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm. Various
	hydrocarbons.

### 11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental No Toxicity:	o data available.			
Ingredient	CAS #	Toxicological Data		
Hydrocarbon propellant	68476-86-8	No data available		
		Inhalation LC50 (4h) Rat 658 mg/L		
Aliphatic hydrocarbon	64741-66-8	Dermal LD50 Rabbit > 3160 ml/kg		
		Dermal LD50 Rabbit > 10000 ml/kg		
Petroleum distillates	8052-41-3	Dermal LD50 Rabbit > 3 g/kg		
		Oral LD50 Rat $> 5$ g/kg		
12. ECOLOGICAL INFORMATION				
Ecological Toxicity: No	o data available			

Ecological Toxicity: Mobility:	No data available No data available		
<b>Ingredient</b> No data available	CAS #	Toxicological Data	

#### 13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

#### 14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable <sup>†</sup>	2.1	Not applicable
* "Limited Quantities" may be enplicable for this transportation mode				

† "Limited Quantities" may be applicable for this transportation mode.

# 15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:				
COMPONENT	CAS #	% BY WEIGHT	Regulatory Body	
No components listed in this section.			SARA Section 313	

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below. No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below. No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

#### **16. OTHER INFORMATION**

Other Information : MSDS Prepared by L. Dean Swartz, MSDS Coordinator

Version Date: 08/10/15

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.