

# Material Safety Data Sheet

## B164 Rubber Parts Cleaner

# Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538	Product Name: Rubber Parts Cleaner Product Code: B164 Version Date: 02/28/11 24-hour emergency phone: 1-800-424-9300 [CHEMTREC]
---	--

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	Exposure Limits OSHA PEL	OTHER
Dimethyl carbinol	67-63-0	400 ppm	400 ppm	500 ppm STEL
2-propanone	67-64-1	500 ppm	1000 ppm	Not established
Glycol ether	111-76-2	20 ppm [skin]	50 ppm [skin]	Not established
Citrus distillates	5989-27-5	Not established	Not established	FDA-GRAS
Petroleum distillates	8052-41-3	100 ppm	500 ppm	Not established

### 3. HAZARDS IDENTIFICATION

#### POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

- Eye : May cause eye irritation. Symptoms may include stinging, tearing, and redness.
- Skin : Skin contact may cause irritation. Symptoms may include redness, discomfort, drying and cracking, or rash. Prolonged or repeated exposure may dry the skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.
- Ingestion : Swallowing small amounts during handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.
- Inhalation : Breathing small amounts during handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: initial Central Nervous System excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects, such as confusion, impaired coordination, coma, and death.

#### POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. This material (or a component) shortens the time onset or worsens the liver and kidney damage induced by other chemicals. Acute lethal exposures in animal studies of a product component has resulted in congestion of organs including kidney, spleen and lungs. Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects. mild, reversible kidney effects. blood abnormalities.

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

#### MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Skin contact may aggravate an existing dermatitis.

#### HMIS® III\* HAZARDOUS WARNINGS:

Health: 2 Flammability: 3 Physical: 0 Personal Protective Equipment: See Section 8

\* See [www.paint.org/hmis](http://www.paint.org/hmis) or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

### 4. FIRST AID MEASURES

- Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
- Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse.
- Ingestion: Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Have victim drink 8 to 10 ounces of water to dilute the material in the stomach.
- Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone.

#### NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; liver; blood forming system;

### 5. FIRE FIGHTING MEASURES

- Fire and/or Explosion Hazards: This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous.
- Fire Fighting Instructions: Use CO<sub>2</sub>, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

Flash Point: -4°F PMCC -20°C PMCC  
 Lower Flammability Limit: 0.7 %  
 Upper Flammability Limit: 6.1 %  
 Autoignition Temperature: 458 DEG F

## 6. ACCIDENTAL RELEASE MEASURES

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

## 7. HANDLING AND STORAGE

**Handling:** Do not use near ignition sources. Use with adequate ventilation. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Do not use near ignition sources. Use with adequate ventilation. Protect container against physical damage. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor.

**Storage:** Keep container tightly closed when not in use. Empty container may contain residues which are hazardous. Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.

**Eye Protection:** Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.

**Skin Protection:** The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

**Respiratory Protection:** A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk liquid	Vapor Density:	[air = 1] 2.91
Appearance:	Clear Colorless	Evaporation Rate:	2-10 (n-Butyl acetate = 1)
Odor:	Mild Sweet odor	Solubility in Water:	Complete; 100%
Specific Gravity:	0.81 (H2O=1)	Boiling Point:	133°F
Vapor Pressure:	3.58 PSIG @ 70°F	pH:	Not applicable

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable.

**Conditions to Avoid:** Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acetaldehyde. Acids. Chlorine. Ethylene oxide. Isocyanates. Strong oxidizing agents. Strong alkalis.

**Decomposition Products:** Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

## 11. DISPOSAL CONSIDERATIONS

**Disposal :** Dispose according to Federal, State and local regulations.

## 12. TRANSPORTATION INFORMATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Isopropanol	UN1219	3	II
IATA	Isopropanol	UN1219	3	II

## 13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.  
 No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.  
 No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

**This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.**