

Safety Data Sheet

A499 Mold Cleaner

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Mold Cleaner
Product Code: A499
Product Use: No data available
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification

Gases under pressure - Refrigerated Liquefied Gas
Flammable Aerosol Category 2
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word

Warning

Hazard Statements

Flammable aerosol.
Contains refrigerated gas; may cause cryogenic burns or injury.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Wear cold insulating gloves/face shield/eye protection.

Response

P302+P352 - If on skin: Wash with plenty of soap and water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a poison center, doctor or medical center if you feel unwell.
Get immediate medical advice/attention.
P321 - Specific treatment (see on this SDS).
If skin irritation occurs: Get medical advice/attention.
Thaw frosted parts with lukewarm water. Do no rub affected area.
If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>Percent</u>
2-propanone	67-64-1	40 - 60
Aliphatic hydrocarbons	142-82-5	20 - 40
Propellant	124-38-9	1-20
Xylene	1330-20-7	1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 2	Flammability: 2	Physical: 0	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone. Seek immediate medical attention. Keep the victim warm and quiet.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); liver; kidney; blood forming system; central nervous system; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous. Containers may rupture or explode under fire conditions.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Empty container may contain residues which are hazardous. Do not store at temperatures above 122 degrees F. Keep away from heat, sparks and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
2-propanone	67-64-1	500 ppm TWA	Not established	Not established
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established
Propellant	124-38-9	5000 ppm	5000 ppm	Not established
Xylene	1330-20-7	150 PPM STEL; 651 MG/M3 STEL	Not established	100ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Sweet odor Light Hydrocarbon	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H2O=1):	0.8
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Insoluble
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	0.2
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	474
Evaporation Rate:	2-10 (n-Butyl acetate = 1)	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	0.3
Percent VOCs (%):	40 - 60		

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acids. Strong oxidizing agents. Alkali. Alkaline earth metals. Metal acetylides. Chromium. Titanium above 550° C. Uranium above 750° C.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. Carbon Monoxide. Oxygen.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.
IARC Carcinogen Designation:	No data available

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
2-propanone	67-64-1	Dermal LD50 GUINEA PIG 9400 UL/KG Oral LD50 Mouse 3 GM/KG Inhalation LC50 Rat 50100 MG/M3 Inhalation LC50 Rat 103 GM/M3 Inhalation LC50 Mouse 200000 ppm Inhalation LC50 Mouse 361 GM/M3 Inhalation LC50 Rat 470000 ppm
Aliphatic hydrocarbons	142-82-5	Dermal LD50 Rabbit 1700 mg/kg
Propellant	124-38-9	Oral LD50 Mouse 2119 mg/kg Oral LD50 Rat 4300 mg/kg
Xylenes	1330-20-7	Inhalation LC50 Rat 5000 ppm Dermal LD50 Rabbit 5000 mg/kg
Ethyl benzene	100-41-4	Inhalation LC50 Mouse 35500 MG/M3

12. ECOLOGICAL INFORMATION

Ecological Toxicity:	No data available
Mobility:	No data available
Degradability:	No data available.

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
2-propanone	67-64-1	Aquatic LC50 (48h) Rainbow Trout = 6100 mg/L 48HR EC50 Daphnia = 7630 mg/L 96H EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 0.0209MG/ Aquatic LC50 (24h) Fish = 4 mg/L
Aliphatic hydrocarbons	142-82-5	

Propellant	124-38-9	48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L No data available Aquatic LC50 (96h) Rainbow Trout 35 mg/L No data available
Xylene	1330-20-7	No data available Aquatic LC50 (96h) MINNOW 24 - 30 mg/L Aquatic LC50 (24h) Daphnia 100 - 1000 mg/L Code:
Ethyl benzene	100-41-4	Aquatic LC50 (96h) Rainbow Trout = 8.4 mg/L 48HR EC50 Daphnia = 9.55 mg/L 72HR EC50 Algae 4.9 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT		Not regulated by agency†	ORM-D	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
Xylene	1330-20-7	1-20	SARA Section 313
Ethyl benzene	100-41-4	0.1- 0.99	SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65



WARNING: This product can expose you to Ethyl benzene, which is(are) known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 01/24/20

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.