



KantStik® Mold Cleaner

Solvent Based Mold Cleaner to Remove Wax and Resin Buildup



Product Description

KantStik® Mold Cleaner is a blend of solvents designed to dissolve and remove most release agents and resin buildup from molds without dulling the surface. It is ideal for preparing mold surfaces for the application of **KantStik®** mold release agents. It is also excellent for cleaning brushes and equipment.

KantStik® Mold Cleaner is useful in removing buildup created by waxes, fluorocarbon base release agents and other polymeric materials; resinous materials such as polyester, epoxy, gel coat, phenolic, acrylic, PS, PC, nylon, vinyl, ABS, PP, HDPE, LDPE, rigid and flexible foam.

Uses

KantStik® Mold Cleaner is used to remove wax and resin buildup.

Direction for Use

Recommended Procedure

KantStik® Mold Cleaner should be applied to the mold surface with a clean non-abrasive cloth. Once the cleaner begins to dissolve the buildup, it should be removed immediately from the mold surface using a second clean cloth while the mold surface is still wet with the cleaner. When the cloth becomes saturated with residue, replace with a new cloth. Repeat the process until the entire residue is removed. Wipe dry. The mold is then ready for application of the release agent and/or to be stored.

CAUTION:

- Flammable liquid
- For Industrial use only
- Avoid breathing vapor, spray mist or prolonged contact with skin. Use only with adequate ventilation. Do not take internally. In confined area, operators should wear respirators or fresh air masks.
- Keep out of reach of children.

Storage and Handling

As with any other flammable product, **KantStik® Mold Cleaner** must be carefully used and kept away from any open flames or sources of heat and ignition. Containers should be kept closed when not in use and stored in a dry, cool area. For more information, please refer to our Material Safety Data Sheet.

Packaging

KantStik® Mold Cleaner is available in:

- Cases of 4x1-gallon Part # P53601RGLXX2
- 5-gallon pails Part # P53605RPLXX2

Technical Assistance

Call: 800-227-5538 or 1 (717) 786-7355

Email: TimeSaver@StonerSolutions.com

Visit: StonerSolutions.com

The information contained in this TDS is believed to be accurate and reliable. It is recommended that each user test the material and procedures prior to initial use. Nothing stated in this TDS is to be construed as a warranty either expressed or implied.