# Material Safety Data Sheet P441 Heavy Duty Mold Release Agent



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND	<b>COMPANY IDENT</b>	TIFICATION			
Stoner Incorporated	Product N	Name:	Heavy Duty Mold Re	Heavy Duty Mold Release Agent	
1070 Robert Fulton Hwy.	Product C	Code:	P441		
Quarryville, PA 17566	Version I	Date:	12/02/11		
1-800-227-5538	24-hour e	emergency phone:	1-800-424-9300 [CHEMTREC]		
2. COMPOSITION / INFORMAT	TION ON INGREDI	ENTS			
			Exposure Limits		
COMPONENT	CAS #	ACGIH TLV	OSHA PEL	<b>OTHER</b>	
/ater	7732-18-5	Not established	Not established	Not established	
J Trade Secret Registry	#80100382-5048P	Not established	Not established	Not established	
blydimethylsiloxane emulsion	MIXTURE	Not established	Not established	Not established	
<b>3. HAZARDS IDENTIFICATION</b>					
hhalation : When heated to temperature: Formaldehyde vapor is harm hazard at concentrations great OTENTIAL CHRONIC [long term] HEALT General Effects: Adverse liver and re Cancer Information: THIS PRODUCT C futagenicity: No data available to MEDICAL CONDITIONS AGGRAVATED I May aggravate liver and kidney. MIS® III* HAZARDOUS WARNINGS: Iealth: 1 Flammability: 0 See www.paint.org/hmis or call the NPCA at	mptoms may include stingi ation. d. If swallowed symptoms s above 150°C in the prese aful by inhalation; irritating ater than 0.75 ppm. Inhalat CH EFFECTS OF OVERE eproductive effects reported CONTAINS NO COMPON o indicate product or any co BY OVEREXPOSURE:	ing, tearing, and redness. may include: Gastrointes nce of air, one of the ing g to eyes; sensitizer to the ion can cause nose, throa XPOSURE: d in animals. IENTS LISTED AS CAR omponents present at grea 0 Person	stinal irritation (such as nausea redients in this product can for e respiratory system; an acute t at, and respiratory tract irritation RCINOGENIC BY IARC, NTI ater than 0.1% is mutagenic or nal Protective Equipment: Se ent rating system.	m formaldehyde vapors. oxicant and a potential can on, coughing and headache. P, OR OSHA 1910(Z) genotoxic.	
4. FIRST AID MEASURES					
Eyes: Immediately flush eyes ge visual difficulty, seek med		or at least 15 minutes wh	ile holding eyelids apart. If sy	mptoms persist or there is	
		rea with plenty of water	for at least 15 minutes. Seek n	nedical attention if	
symptoms persist. Seek m				activation attention in	
	cal facility, or poison conti				
igestion: Contact a physician, medi		of center mineuratery.			
nhalation: Remove to fresh air. If not	t breathing, give artificial r		s difficult, give oxygen.		
nhalation: Remove to fresh air. If not NOTES TO PHYSICIAN:	t breathing, give artificial r		s difficult, give oxygen.		
nhalation: Remove to fresh air. If not NOTES TO PHYSICIAN: Treatment is symptomatic and supportive.			s difficult, give oxygen.		
halation: Remove to fresh air. If not NOTES TO PHYSICIAN: Treatment is symptomatic and supportive. <b>5. FIRE FIGHTING MEASURES</b>	3	respiration. If breathing is	s difficult, give oxygen.	ant ha formad ( 8 10)	

# Fire and/or Explosion Hazards: Product is a water base material and is not ignitable.Hazardous decomposition products may be formed (see Sec.10). Fire Fighting Instructions: Use water spray, foam, dry chemical, or CO2. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus. Flash Point: None°F PMCC None°C PMCC Lower Flammability Limit: No data available Upper Flammability Limit: No data available Autoignition Temperature: No data available

### 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

### 7. HANDLING AND STORAGE

Handling:	Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid contact with eyes. Spilled
	material is quite slippery.
Storage:	Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Keep from
	extreme temperatures. Keep from freezing. Do not store at temperatures above 80 degrees F.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:

Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known,

Eye Protection:

suspected or apparent adverse effects).

Skin Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available. The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact

Respiratory Protection:

with skin. No respiratory protection required under normal conditions of use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk liquid	Vapor Density:	[air = 1] 0.99
Appearance:	Clear Colorless White Straw yellow	Evaporation Rate:	0.02-0.1 (n-Butyl acetate = 1)
Odor:	None to very faint	Solubility in Water:	Not determined
Specific Gravity:	1.00 (H2O=1)	Boiling Point:	212°F
Vapor Pressure:	.36 PSIG @ 70°F	pH:	Not applicable

### 10. STABILITY AND REACTIVITY

Chemical Stability: Conditions to Avoid: Decomposition Products:

None known. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Oxides of siloxanes. Formaldehyde.

### 11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

Stable.

12. TRANSPORTATION INFORMATION						
<b>Agency</b> DOT IATA	<b>Proper Shipping name</b> Not regulated by agency Not regulated by agency	UN Number	Hazard Class	Packing Group		
13. RE	GULATORY INFORMAT	ION				
COMPON	1 0	chemicals that are subject to reporting CAS # % BY	WEIGHT Regul	g regulatory bodies listed below: atory Body Section 313		
0	This product may contain chemicals nents listed in this section.	known to the State of California to ca		55 Cancer		
0	This product may contain chemicals nents listed in this section.	known to the State of California to ca		v. 65 Birth Defects		
A 11 00mm0	ments of this meduat are listed on th	TECA inventory				

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.