

Material Safety Data Sheet

A324 Rapid Release™

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Rapid Release™
Product Code: A324
Version Date: 11/29/13
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	Exposure Limits	
			OSHA PEL	OTHER
Hydrocarbon propellant	68476-86-8	Not established	Not established	Not established
NJ Trade Secret Registry	#80100382-5096P	Not established	Not established	Not established
Aliphatic hydrocarbon	64741-66-8	Not established	500ppm TWA	300ppm TWA-Mfr. Recommended
Petroleum distillates	8052-41-3	100 ppm TWA	500 ppm	Not established

3. HAZARDS IDENTIFICATION

POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

Eye : May cause frostbite and irritation. May cause eye irritation. Symptoms may include stinging, tearing, and redness.

Skin : Liquid may cause frostbite. Skin contact may cause irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, discomfort, drying and cracking, or rash. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion : Frostbite of the lips and mouth may result from contact with the liquid. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage. Swallowing small amounts during handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation : May cause nausea, vomiting, coughing and pulmonary irritation. Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination. Breathing small amounts during handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: initial Central Nervous System excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects, such as confusion, impaired coordination, coma, and death.

POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: Prolonged or repeated exposure can cause drying, defatting, and dermatitis of the skin. Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Skin contact may aggravate an existing dermatitis.

HMS® III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 4 Physical: 0 Personal Protective Equipment: See Section 8

* See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: For liquid contact, treat for frostbite if necessary. In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.

Ingestion: Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.

Fire Fighting Instructions: Use CO₂, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.

Flash Point: Not applicable °F PMCC °C PMCC

Lower Flammability Limit: Not applicable
 Upper Flammability Limit: Not applicable
 Autoignition Temperature: Not applicable
 Aerosol Flame Projection Test: Extremely flammable aerosol, as determined by ASTM D 3065-94. Do not use near ignition sources such as sparks or open flames.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: This material can be harmful or irritating. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not use near ignition sources.

Storage: Do not store at temperatures above 120 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation is required to maintain operator exposure below published exposure limits. Ventilation should be adequate to prevent exposures above the limits indicated in "Section 8" of this MSDS (from known, suspected or apparent adverse effects).

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Vapor Density:	[air = 1] 2.01
Appearance:	Cloudy white	Evaporation Rate:	0.1-0.5 (n-Butyl acetate = 1)
Odor:	Petroleum solvent	Solubility in Water:	Negligible; 0-1%
Specific Gravity:	0.53 (H ₂ O=1)	Boiling Point:	No data available °F
Vapor Pressure:	56.00 PSIG @ 70 °F	pH:	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

11. DISPOSAL CONSIDERATIONS

Disposal: Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Aerosols, flammable *	UN1950	2.1	Not applicable
IATA	Aerosols, flammable *	UN1950	2.1	Not applicable
IMDG	Aerosols, flammable *	UN1950	2.1	Not applicable

* "Limited Quantities" may be applicable for this transportation mode.

13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.	
No components listed in this section.	Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.	
No components listed in this section.	Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.