

Material Safety Data Sheet

A163 Plastic Surface Cleaner

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538	Product Name: Plastic Surface Cleaner Product Code: A163 Version Date: 02/17/14 24-hour emergency phone: 1-800-424-9300 [CHEMTREC]
---	---

2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	EXPOSURE LIMITS	OTHER
Hydrocarbon propellant	68476-86-8	Not established	Not established		Not established
NJ Trade Secret Registry	#80100382-5094P	400 ppm	400 ppm		Not established
Glycol ether	111-76-2	20 ppm [skin]	50 ppm [skin]		Not established
Dimethyl carbinol	67-63-0	200 ppm	Not established		200 ppm 8 hr TWA

3. HAZARDS IDENTIFICATION

POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

Eye : May cause frostbite and irritation. May cause eye irritation. Symptoms may include stinging, tearing, and redness.
Skin : Liquid may cause frostbite. Skin contact may cause irritation. Symptoms may include redness, discomfort, drying and cracking, or rash.
Ingestion : Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.
Inhalation : May cause nausea, vomiting, coughing and pulmonary irritation. Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache. Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: initial Central Nervous System excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects, such as confusion, impaired coordination, coma, and death. Breathing small amounts during handling is not likely to cause harmful effects.

POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: Upon prolonged or repeated use, can be associated with central nervous system damage. This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. Acute lethal exposures in animal studies of a product component has resulted in congestion of organs including kidney, spleen and lungs. mild, reversible kidney effects. mild, reversible liver effects. blood abnormalities. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Respiratory related chronic illnesses (i.e. asthma, etc.). Skin contact may aggravate an existing dermatitis.

HMSI® III* HAZARDOUS WARNINGS:

Health: 2 Flammability: 2 Physical: 0 Personal Protective Equipment: See Section 8

* See www.paint.org/hmsi or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
Ingestion: Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions); liver; kidney; skin;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: Product is water based material, containing minor amounts of flammable ingredients. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.

Fire Fighting Instructions: Use CO₂, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

Flash Point: Not applicable °F PMCC °C PMCC

Lower Flammability Limit: Not applicable

Upper Flammability Limit: Not applicable
 Autoignition Temperature: Not applicable °F
 Aerosol Flame Projection Test: Non-flammable aerosol, as determined by ASTM D3065-94. However, this product contains components which may be ignited under certain circumstances. Do not use near ignition sources such as sparks or open flames.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Place waste material into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: This material can be harmful or irritating. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Wash hands thoroughly after handling. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Do not use near ignition sources. Avoid prolonged or repeated breathing of vapor. Do not use near ignition sources. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage.

Storage: Do not store at temperatures above 120 degrees F. Keep from freezing. Store at temperatures between 45° and 99° F. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation is required to maintain operator exposure below published exposure limits. Ventilation should be adequate to prevent exposures above the limits indicated in "Section 8" of this MSDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Vapor Density:	[air = 1] 1.08
Appearance:	Clear Colorless	Evaporation Rate:	0.1-0.5 (n-Butyl acetate = 1)
Odor:	Slight Alcohol	Solubility in Water:	Complete; 100%
Specific Gravity:	0.99 (H2O=1)	Boiling Point:	No data available°F
Vapor Pressure:	52.00 PSIG @ 70°F	pH:	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Strong alkalis. Acetaldehyde. Acids. Chlorine. Ethylene oxide. Isocyanates.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Oxides of sulfur.

11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Aerosols, non-flammable *	UN1950	2.2	Not applicable
IATA	Aerosols, non-flammable *	UN1950	2.2	Not applicable
IMDG	Aerosols, non-flammable *	UN1950	2.2	Not applicable

* "Limited Quantities" may be applicable for this transportation mode.

13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.
 No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.
 No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.